

**ОБЩЕСТВО С ОГРАНИЧЕННОЙ ОТВЕТСТВЕННОСТЬЮ  
«ЕНИСЕЙСКИЙ ФАНЕРНЫЙ КОМБИНАТ»**

662500, Россия, Красноярский край, г. Сосновоборск, ул. Заводская, 1.  
тел. (391) 274-87-79. факс (391) 274-87-75. e-mail: efk@efk-kr.ru

**DECLARATION OF PERFORMANCE No 2**

1. Softwood plywood, Type FSF, thickness 9-40 mm
2. Batch number: see packaging of the product
3. Plywood for internal use as structural component in humid conditions – EN 13986:2004 (4.2), EN 636-2 S
4. Manufacturer - Eniseisky plywood factory, 662500, Russia, Krasnoyarsk region, Sosnovoborsk city, Zavodskaya Street, 1.
5. Not applicable
6. EN 13986:2004. 2+ System (for use as a material for building)
7. The notified body 1075 of Amtliche Materialprüfungsanstalt (MPA) der Freien Hansestadt Bremen ein Geschäftsbereich der Stiftung Institut für Werkstofftechnik Paul-Feller-Str. 1, 28199, Bremen, DEUTSCHLAND made initial survey of manufacturer and continuous supervision, control and an assessment of production control of plant, according to system 2+ and issued the Certificate on production control of plant 1075-CPD-Z388-1/12
8. Not applicable
9. The declared characteristics

The main characteristics	The minimum results at a plywood thickness				The approved technical specification
	9 mm	12 – 18 mm	21 – 27 mm	30 – 40 mm	
Tensile strength along the fiber direction	20 N/MM <sup>2</sup>	20 N/MM <sup>2</sup>	15 N/MM <sup>2</sup>	10 N/MM <sup>2</sup>	EN 636:2012 Table 1 and 2
Tensile strength to the fiber direction	5 N/MM <sup>2</sup>	5 N/MM <sup>2</sup>	10 N/MM <sup>2</sup>	10 N/MM <sup>2</sup>	
The modulus of elasticity along the fiber	4000 N/MM <sup>2</sup>	4000 N/MM <sup>2</sup>	3000 N/MM <sup>2</sup>	3000 N/MM <sup>2</sup>	EN 636:2012, EN 314-2
The modulus of elasticity across the fiber	500 N/MM <sup>2</sup>	1000 N/MM <sup>2</sup>	1500 N/MM <sup>2</sup>	1500 N/MM <sup>2</sup>	
Bonding quality	Class 3				EN 314-2
Humidity	5 – 12 %				EN 322
Density	≥400 кг/м <sup>3</sup>				EN 323
Fire resistance	D-2s, d0				EN 13986/13501-1
Formaldehyde content	E1				EN 717-2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

General director  
Eniseisky plywood mill LLC



Petnyunas A.A.

24. May 2013